
## TEMPORARY TRAFFIC CONTROL TYPICAL APPLICATION THIS DRAWING SHALL BE USED IN COMBINATION WITH THE GENERAL NOTES AT THE BEGINNING OF MOBK STANDARDS NO. MD 104.00. 200 E NOTE: DAOR FLAGGER SHALL NEVER BE STATIONED MORE THAN 1000' AWAY FROM THE ADVANCE ONE LANE FLAGGER SIGN. KEY: CHANNELIZING DEVICES SIGN SUPPORT FACE OF SIGN DIRECTION OF TRAFFIC **END** ROAD WORK WORK SITE (OPTIONAL) INTERVAL FLAGGER 50, 10, ROAD WORK END (OPTIONAL) 200 NE LANE ROAD 1500 F 100 ROAD WORK MIL



10-1-01

REVISED

REVISED

REVISED

REVISED

REVISED

StateHighway

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES FLAGGING OPERATION/2-LANE, 2-WAY GREATER THAN 40 MPH/15 MIN - 12 HRS. OR DAYTIME ONLY

STANDARD NO.

MD 104.31-01